

## CLAIM AMENDMENTS

Claims 1-6 (cancelled).

Claim 7 (new): A stroller adapted for securely supporting a car seat which has a fastening slot of a securing arrangement for a seat belt of a vehicle to fasten in position, comprising:

a stroller frame comprising a supporting frame having two front frame legs, a boundary frame frontwardly extended from said supporting frame and a handle frame upwardly extended from said supporting frame;

a regular seat comprising a seat support horizontally supported by said supporting frame and a back support upwardly extended from a rear portion of said seat support, wherein a receiving cavity, having a size adapted for substantially disposing said car seat therein, is formed between said boundary frame and said regular seat; and

a car seat fastening arrangement comprising:

a connecting unit provided at a rear side of said back support of said regular seat, wherein said connecting unit comprises at least a unit connector; and

a holding belt having a first end connected to said connecting unit and a second end affixed with a belt connector detachably fastened with said unit connector to form a holding loop having a size enough for encirclingly holding said car seat on said stroller through said fastening slot of said car seat to retain said car seat on said stroller at a position that a baby or a young child sat on said car seat is facing rearward.

Claim 8 (new): The stroller, as recited in claim 7, further comprising a buckle plug affixed to said second end of said holding belt and a buckle socket provided at said unit connector to detachably connect with said buckle plug so as to form said holding loop of said holding belt for securing with said car seat.

Claim 9 (new): The stroller, as recited in claim 7, wherein said car seat fastening arrangement further comprises means for selectively adjusting said size of said holding loop of said holding belt for tightly holding said car seat with said stroller frame.

Claim 10 (new): The stroller, as recited in claim 8, wherein said car seat fastening arrangement further comprises means for selectively adjusting said size of said holding loop of said holding belt for tightly holding said car seat with said stroller frame.

Claim 11 (new): The stroller, as recited in claim 9, wherein said adjustment means comprises at least an adjusting member coupled on said holding belt to selectively lock up said belt connector at a position along said holding belt such that said size of said holding loop is adjusted when said length of between said belt connector and said first end of said holding belt is adjusted.

Claim 12 (new): The stroller, as recited in claim 10, wherein said adjustment means comprises at least an adjusting member coupled on said holding belt to selectively lock up said belt connector at a position along said holding belt such that said size of said holding loop is adjusted when said length of between said belt connector and said first end of said holding belt is adjusted.